

Características Bluetti AC200MAX

Specifications

BATTERY INFO	Capacity:	2,048Wh (51.2V, 40Ah)
	Cell Chemistry:	LiFePO4 (Lithium Iron Phosphate)
	Lifecycle:	3500+(to 80%),6000+(to 50%)
	Management System:	BMS, Over Voltage Protection, Short Circuit Protection
OUTPUT	AC Output:	230V, 50Hz, 2200W In Total
	USB Output:	2*5V/3A USA-A 2*18W USB-A 18W 1*100W USB-C
	DC Output:	1*12V/30A Super DC 1*12V/10A Cigarette Lighter Port 2*12V/10A DC 5521 Output
	Wireless Charging:	2*15W Wireless Charging Pad
INPUT	AC Adapter Input:	500W.
	Solar Input:	900W Max., VOC 10-145VDC, 15A
	Car Input:	12/24V from Cigarette Lighter Port
	Max Input:	1,400W, with AC+Solar Input
RECHARGE TIME	AC Adapter (500W):	≈5.5~6 Hours
	Solar (900W):	≈3~3.5 Hours (With prime sunshine, ideal orientation and low temperature)
	12V/24V Car Outlet (100W/200W):	≈10 or 20 Hours
	AC Adapter + Solar (1400W):	≈2.0~2.5 Hours (With prime sunshine, ideal orientation and low temperature)
	Dual AC Adapters (800W):	≈3~3.5 Hours (Extra adapter is REQUIRED)
GENERAL	Scalability:	Expandable Up to 2 x B230 or 2 x B300
	Weight:	61.9lbs (28.1kg)
	Dimensions (LxWxD):	16.5 x 11 x 15.2in (42 x 28 x 38.65cm)
	Operating Temperature:	-4-104°F (-20-40°C)
	Storage Temperature:	14-113°F (-10-45°C)
	Certifications:	UL Standard, CEC, DOE, FCC, CA Prop 65
	Warranty:	2+2 Years

