

Características Bluetti EB55

Specifications

BATTERY INFO	Capacity:	537Wh (22.4V, 24Ah)
	Type:	LiFePO4 (Lithium Iron Phosphate)
	Life Cycles:	2,500+ Cycles to 80% Original Capacity
	Shelf-life:	Recharge to 80% Every 3-6 Months
	Management System:	MPPT Controller, BMS, etc.
PORTS	2*AC Output:	220-240v,700W
	4*USB-A Output:	5V,3A
	1*Car Port:	DC 12V,10A
	2*DC Outputs:	12V, 10A, 5.5mm x 2.1mm
	1*Type-C PD Outputs:	100W
	1*Wireless Charging Pad:	15W
RECHARGE TIMES	AC Adapter (200W):	≈3-3.5 Hours
	Solar (200W):	≈3-3.5 Hours (With prime sunshine, ideal orientation and low temperature)
	12V/24V Car Outlet (98.4W/196.8W):	≈6-6.5 Hrs or 3-3.7 Hours
	AC+ Solar (400W):	≈1.8~2.3 Hours (With prime sunshine, ideal orientation and low temperature)
	Dual AC (400W):	≈1.8~2.3 Hours (Extra adapter is REQUIRED)
GENERAL	Weight:	16.5lbs (7.5Kg)
	Dimensions (LxWxD):	10.94 x 7.87 x 7.79in (27.8 x 20 x 19.8cm)
	Operating Temperature:	14-104°F (-10-40°C)
	Storage Temperature:	14-113°F (-10-45°C)
	Certifications:	UL, CEC, DOE, FCC, CA Prop 65
	Warranty:	24 Months

