

Características Batería Bluetti B300S

Specifications

BATTERY INFO		
Capacity:	3,072Wh (51.2V, 60Ah)	
Cell Chemistry:	LiFePO4 (Lithium Iron Phosphate)	
Life Cycles:	3,500+ Cycles to 80% Original Capacity	
Shelf-life:	Recharge to 80% Every 3-6 Months	
Management System:	MPPT Charge Controller, BMS, etc.	
OUTPUT		
USB-C Port:	1 x 100W Max.	
USB-A Port:	1 x 18W	
DC Outlets:	1 x 12V (Car Outlet) *All regulated.	
INPUT		
AC Input:	500W Max.	
Solar Input:	500W Max., VOC 12-60VDC, 10A	
Car Input:	12/24V from Cigarette Lighter Port	
Maximum Input:	1,000W, with D050S DC Charging Enhancer	
GENERAL		
Simultaneous Recharge & Discharge:	Yes	
Weight:	79.6lbs (36.1kg)	
Dimensions (LxWxD):	20.5 x 12.5 x 10.5in (52 x 32 x 26.6cm)	
Operating Temperature:	-4°F-104°F (-20°C-40°C)	
Storage Temperature:	-4°F-104°F (-20°C-40°C)	
Certification:	UL Standard, CEC, DOE, FCC, CA Prop 65	
Warranty:	48 Months	